

MailEnable PowerShell Reference

14th April 2020

Overview

MailEnable's PowerShell interface allows system administrators and developers to manage MailEnable via PowerShell.

Administrators can perform typical actions via scripts and can develop and extend these to these commands via scripting. PowerShell significantly improves automation and integrated management of MailEnable.

PowerShell support is available for all editions of MailEnable since version 9.5.

Launching PowerShell

You can launch PowerShell either by:

1. Selecting **Windows PowerShell** from the Start screen, or:
2. Selecting **Windows PowerShell** from the taskbar.

Executing MailEnable PowerShell Commands

Once PowerShell opens, use the following command to add the MailEnable PowerShell snap-in to the current PowerShell session:

```
Add-PSSnapin MailEnable.Provision.Command
```

You can then issue specific commands depending on the area of MailEnable you wish to configure. You can add this to your PowerShell profile so this line is not needed each time.

The first command to issue is the Help command. It provides a comprehensive list of the settings that can be manipulated via PowerShell.

```
Example: PS> Get-MailEnablePlatform -Help "*"
```

The asterisk tells PowerShell to return all settings.

You can also filter them by simply providing part of the setting name.

```
Example: PS>Get-MailEnablePlatform -Help "Skin"
```

```
SettingId      : sysSkinCatalogueEnabled
SettingType    : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose        : Determines whether the Management Console shows an online skin catalogue
```

The Help command returns the SettingId (the name of the setting), and the SettingType (which is the Command that is used to Set it).

PowerShell Commands are prefixed with the action you wish to perform, i.e.: New, Get, Set, Remove, etc.

As such, to enable the Skin Catalogue within MailEnable, you would execute the following command:

```
Set-MailEnablePlatform -Setting sysSkinCatalogueEnabled -Value 1
```

MailEnable PowerShell Command Overview

MailEnable's PowerShell interface is compact but provides the ability to change thousands of settings. It provides the following cmdlets, each of which can be passed parameters to perform configuration changes.

The platform cmdlets manage server wide settings and options, such as service configuration.

Get-MailEnablePlatform

Set-MailEnablePlatform

The postoffice cmdlets manage postoffices and their settings.

Get-MailEnablePostoffice

Set-MailEnablePostoffice

Add-MailEnablePostoffice

Remove-MailEnablePostoffice

The mailbox cmdlets manage users and their settings.

Get-MailEnableMailbox

Set-MailEnableMailbox

Add-MailEnableMailbox

Remove-MailEnableMailbox

The domain cmdlets manage domain settings

Get-MailEnableDomain

Set-MailEnableDomain

Add-MailEnableDomain

Remove-MailEnableDomain

The address map cmdlets

MailEnableAddressMap - manage email addresses

The group cmdlets

MailEnableGroup - manage distribution groups

The group member cmdlets

MailEnableGroupMember - manage distribution group membership

The list cmdlets

MailEnableList - manage distribution lists

The list member cmdlets

MailEnableListMember - manage distribution group membership

PowerShell Command Line Examples

The following examples show some of the more common commands you may wish to execute via PowerShell.

Before executing the commands, you should ensure that the extension is loaded using the following PowerShell command: Add-PSSnapin MailEnable.Provision.Command

Platform Examples

Get the current IMAP alternate port number

```
Get-MailEnablePlatform -Setting imapAlternatePort
```

Set the current IMAP alternate port number

```
Set-MailEnablePlatform -Setting imapAlternatePort -Value 993
```

Postoffice Examples

Create a new Postoffice with domain

```
New-MailEnablePostoffice -Domain "example.com" -Postoffice "example.com"
```

Create a new Postoffice, domain and mailbox as ADMIN user

```
New-MailEnablePostoffice -Domain "example.com" -Postoffice "example.com" -AdminUserName "adminuser" -AdminPassword "pwd1234"
```

Create a new Postoffice, domain and mailbox as ADMIN user, and mailbox as USER user

```
New-MailEnablePostoffice -Domain "example.com" -Postoffice "example.com" -AdminUserName "adminuser" -AdminPassword "pwd1234" -UserName "sales" -Password "pwd1234"
```

Create a new Postoffice, domain and multiple mailboxes

```
New-MailEnablePostoffice -Domain "example.com" -Postoffice "example.com" -UserName "sales,support,accounts,marketing" -Password "pwd1234,pwd4321,pwd6789,pwd3456"
```

Disable a Postoffice

```
Set-MailEnablePostoffice -Postoffice "example.com" -Setting poEnabled -Value 0
```

Enable ActiveSync for a Postoffice

```
Set-MailEnablePostoffice -Postoffice "example.com" -Setting poActiveSync -Value 1
```

Get the state of ActiveSync for a Postoffice

```
Get-MailEnablePostoffice -Postoffice "example.com" -Setting poActiveSync
```

Mailbox Examples

Create a new mailbox for a Postoffice/domain

```
New-MailEnableMailbox -Mailbox "Joe" -Domain "example.com" -Password "password" -Right "USER"
```

Change user password

```
Set-MailEnableMailbox -Postoffice "example.com" -Mailbox "Joe" -Setting "mailboxPassword" -Value "blah123"
```

Change user display name

```
Set-MailEnableMailbox -Postoffice "example.com" -Mailbox "Joe" -Setting "mailboxDisplayName" -Value "mydisplayname"
```

Change user timezone

```
Set-MailEnableMailbox -Postoffice "example.com" -Mailbox "Joe" -Setting "mailboxTimeZone" -Value "Mountain Standard Time"
```

Set a user's mailbox quota to 50MB

```
Set-MailEnableMailbox -Postoffice MailEnable -Mailbox Andrew -Setting mailboxLimit -Value 50000
```

Set a user's mailbox quota to unlimited

```
Set-MailEnableMailbox -Postoffice MailEnable -Mailbox Andrew -Setting mailboxLimit -Value "-1"
```

Disable login access to a mailbox

```
Set-MailEnableMailbox -Postoffice MailEnable -Mailbox Andrew -Setting mailboxLoginStatus -Value 0
```

Disable a mailbox (prevents message delivery to a mailbox)

```
Set-MailEnableMailbox -Postoffice MailEnable -Mailbox Andrew -Setting mailboxStatus -Value 0
```

Domain Examples

List the domains for the platform

```
Get-MailEnableDomain
```

Redirect domain to another host

```
Set-MailEnableDomain -Domain "example32.com" -Setting "domainRedirectionHosts" -Value  
"test.example.com,test2.example.com"
```

```
Set-MailEnableDomain -Domain "example32.com" -Setting "domainRedirectionStatus" -Value "1"
```

Disable domain redirection

```
Set-MailEnableDomain -Domain "example32.com" -Setting "domainRedirectionStatus" -Value "0"
```

List domains

```
Get-MailEnableDomain -Domain "example32.com"
```

Get properties of a domain object

```
Get-MailEnableDomain -Domain "example32.com"
```

Get a setting for a domain

```
Get-MailEnableDomain -Domain "example32.com" -Setting "domainRedirectionStatus"
```

List the domains for a given Postoffice

```
Get-MailEnableDomain -Postoffice "example.com"
```

Mail Distribution Group Examples

Create a new group

```
New-MailEnableGroup -Postoffice "example.com" -GroupName "myGroup222" -EmailAddress  
"mygroup@example.com"
```

Remove a group

```
Remove-MailEnableGroup -Postoffice "example.com" -GroupName "myGroup222"
```

Add a member to a group

```
New-MailEnableGroupMember -Postoffice "example.com" -GroupName "myGroup222" -EmailAddress  
"member@example.com"
```

Remove a member from a group

```
Remove-MailEnableGroupMember -Postoffice "example.com" -GroupName "myGroup222" -EmailAddress  
"member@example.com"
```

List the members of a group

```
Get-MailEnableGroupMember -Postoffice "example.com" -GroupName "myGroup222"
```

Mail Distribution List Examples

Create a Distribution List

```
New-MailEnableList -Postoffice "example.com" -ListName "myList222" -EmailAddress "mylist@example.com" -  
Description "my example list"
```

Remove list

```
Remove-MailEnableList -Postoffice "example.com" -ListName "myList222"
```

Add a member to a list

```
New-MailEnableListMember -Postoffice "example.com" -ListName "myList222" -EmailAddress  
"member@example.com"
```

Remove a member from a list

```
Remove-MailEnableListMember -Postoffice "example.com" -ListName "myList222" -EmailAddress  
"member@example.com"
```

List the members of a list

```
Get-MailEnableListMember -Postoffice "example.com" -ListName "myList222"
```

Mail Address Examples

Add a mapping to an SMTP address to a local mailbox

```
New-MailEnableAddressMap -EmailAddress "Email@example.com" -Postoffice "example.com" -Mailbox "Joe"
```

Remove a mapping to an SMTP address to a local mailbox

```
Remove-MailEnableAddressMap -EmailAddress "Email@example.com" -Postoffice "example.com" -Mailbox "Joe"
```

Get the Email addresses associated with a mailbox

```
Get-MailEnableAddressMap -Postoffice "example.com" -Mailbox "Joe"
```

PowerShell Script Example

The following example shows how you can perform batch operations within PowerShell scripts.

The example below shows how you can iterate all the postoffices within MailEnable and enable public folder support. You can use the PowerShell ISE to develop your PowerShell scripts.

```
#####  
# Example script: Enable Public Folders for all Postoffices  
#####  
# Ensure the snapin module is loaded (if it is not already)  
if ((Get-PSSnapin -Name MailEnable.Provision.Command -ErrorAction SilentlyContinue) -eq $null )  
{  
    Add-PsSnapin MailEnable.Provision.Command  
}  
# Get the list of PostOffices  
$lstPostoffices = Get-MailEnablePostoffice  
  
ForEach($oPostoffice in $lstPostoffices)  
{  
    # Set the Public Folder Status Flag for each Postoffice  
    Set-MailEnablePostoffice -Postoffice $oPostoffice.Name -Setting "poPublicFolders" -Value 1  
}
```

A similar script can also be used to change settings on all mailboxes in a postoffice. The following script disables webmail for all mailboxes in a postoffice. Although the postoffice setting is checked first, this may be useful if you need to disable a feature for all mailboxes and enable ones on a case by case basis.

```
# Ensure the snapin module is loaded (if it is not already)  
if ((Get-PSSnapin -Name MailEnable.Provision.Command -ErrorAction SilentlyContinue) -eq $null)  
{  
    Add-PSSnapin MailEnable.Provision.Command  
}  
  
# Get the list of mailboxes in the postoffice  
$lstMailboxes = Get-MailEnableMailbox -Postoffice "example.com"  
  
ForEach($oMailbox in $lstMailboxes)  
{  
    # Set the webmail setting  
    Set-MailEnableMailbox -Postoffice "example.com" -Mailbox $oMailbox.MailboxName -Setting  
"mailboxWebMail" -Value 0  
}
```

More Information

For more information on configuring MailEnable via PowerShell and integrating with other cmdlets, please refer to the Microsoft PowerShell reference.

Settings

A complete list of the available settings are below.

SettingId : imapListenPort

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : imapListenPortSSLEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : imapAlternatePortEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : imapAlternatePort

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : imapAlternatePortSSLEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : imapExtensions

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : checklist

Purpose :

SettingId : imapIdleTimeout

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : seconds

Purpose :

SettingId : imapLimitThreads

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : imapMaximumRecvThreads

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : threads

Purpose :

SettingId : imapIPV6

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : imapbinding

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : checklist

Purpose :

SettingId : imapNonIdleTimeoutEnable

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : imapPublicFoldersEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : imapEnforceQuotas
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : imapDebugEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : imapDebugLogLevel
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : imapDebugLogFileDirectory
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl : path
Purpose :

SettingId : imapPreLogInboundRequests
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : imapActivityLogEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : imapActivityLogDirectory
SettingType : MailEnablePlatform
SettingDataType : string

SettingControl : path

Purpose :

SettingId : imapW3CLoggingEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : imapW3CLoggingRolloverFrequency

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : imapW3CLoggingDirectory

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : path

Purpose :

SettingId : imapLoginDisabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : imapStartTLS

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : imapAllowPlainAuthentication

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpLocalDomainName

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : domainname

Purpose :

SettingId : smtpLocalDNSServerList

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : dnsserverlist

Purpose :

SettingId : smtpBadMailNotificationSenderAddress

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : emailaddress

Purpose :

SettingId : smtpHostName

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : domainname

Purpose :

SettingId : smtpDomainKeysStatus

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpMaximumSendThreads

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : threads

Purpose :

SettingId : smtpOutgoingPollInterval

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : seconds

Purpose :

SettingId : smtpCommandTimeout
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : seconds
Purpose :

SettingId : smtpFirstMessageRetryInterval
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : minutes
Purpose :

SettingId : smtpSecondMessageRetryInterval
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : minutes
Purpose :

SettingId : smtpThirdMessageRetryInterval
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : minutes
Purpose :

SettingId : smtpSubsequentMessageRetryInterval
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : minutes
Purpose :

SettingId : smtpOutboundFailedMessageLifetime
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : hours
Purpose :

SettingId : smtpNoNDRGeneration
SettingType : MailEnablePlatform
SettingDataType : dword

SettingControl : select

Purpose :

SettingId : smtpNDRinbound

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpNDRCopyTo

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl :

Purpose :

SettingId : smtpNoDelayNotificationGeneration

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : smtpRestrictConcurrentOutbound

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpConcurrentOutboundLimit

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : smtpNoDelayNotificationGeneration

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpDelayNotificationTime

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : minutes

Purpose :

SettingId : smtpDropFolderStatus

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpDropFolderPath

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : path

Purpose :

SettingId : smtpConnectorAuthenticationSource

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : smtpConnectorUsername

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl :

Purpose :

SettingId : smtpConnectorPassword

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : password

Purpose :

SettingId : smtpListenPort

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : smtpListenPortSSLEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpListenPortRelayMode
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpListenPortAuthenticationMode
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : smtpAlternatePortEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpAlternatePort
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : dword
Purpose :

SettingId : smtpAlternatePortSSLEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpAlternatePortRelayMode
SettingType : MailEnablePlatform
SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpAlternatePortAuthenticationMode

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : smtpAdditionalPorts

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : datatable

Purpose :

SettingId : smtpIPV6

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpbinding

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : checklist

Purpose :

SettingId : smtpDebugEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpDebugLogLevel

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : smtpDebugLogFileDirectory

SettingType : MailEnablePlatform
SettingDataType : string
SettingControl : path
Purpose :

SettingId : smtpActivityLogEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : smtpActivityLogDirectory
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl : path
Purpose :

SettingId : smtpW3CLoggingEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : smtpW3CLoggingRolloverFrequency
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : smtpW3CLoggingDirectory
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl : path
Purpose :

SettingId : smtpGreylistIPAddresses
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : smtpGreylistEntryExpirationTime
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : minutes
Purpose :

SettingId : smtpGreylistEntryRetryDelay
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : minutes
Purpose :

SettingId : smtpGreylistIPAddressMode
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : smtpAllowGreylistExceptions
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpBypassGreylistingOnSPF
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpLimitOutboundMessageSize
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpMaximumOutboundMessageSize
SettingType : MailEnablePlatform
SettingDataType : dword

SettingControl : bytes

Purpose :

SettingId : smtpForceOutboundInterface

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpOutboundInterface

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : select

Purpose :

SettingId : smtpOutboundTLSMode

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpNoTLSFallback

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpBlacklistEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpBlacklistProcessingOrder

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : checklist

Purpose :

SettingId : smtpRDNSHandlingMode

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : smtpSBLEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpSBLProcessingOrder

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : checklist

Purpose :

SettingId : smtpURISBLMode

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : smtpAllowSMTPRelay

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpAllowRelayForAuthenticatedSenders

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpAllowRelayForLocalSenderAddresses

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpAllowRelayForPrivilegedIPRanges
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpRelayAccess
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : smtpBlockReportedIPAddresses
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpReportedIPAddressThreshold
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : dword
Purpose :

SettingId : smtpReportedIPAddressExpiration
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : hours
Purpose :

SettingId : smtpRequireAuthenticationForLocalDelivery
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : smtpCommandAUTH
SettingType : MailEnablePlatform
SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpCommandHELO

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpCommandEHLO

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpCommandMAIL

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpCommandRCPT

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpCommandNOOP

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpCommandTURN

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpCommandEXPN

SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpCommandVRFY
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpCommandSOML
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpCommandSAML
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpCommandSEND
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpCommandRSET
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpCommandHELP
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpCommandDATA
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpCommandQUIT
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpCommandXCLIENT
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : authPOPBeforeSMTP
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : authPOPBeforeSMTPTime
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : dword
Purpose :

SettingId : authDomainAliasStatus
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpIPAccess
SettingType : MailEnablePlatform
SettingDataType : dword

SettingControl : select

Purpose :

SettingId : smtpTLSStatus

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpNTLMAuthStatus

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpCRAMMD5AuthStatus

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpPLAINAuthStatus

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpAuditOutbound

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpForwardAllOutboundEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpOutboundAuthenticationStatus

SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpOutboundUsername
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl :
Purpose :

SettingId : smtpOutboundPassword
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl : password
Purpose :

SettingId : smtpSmartHostProcessingMode
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpForwardAllOutboundHost
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl :
Purpose :

SettingId : smtpAlternateCatchAllHeaderEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpAlternateCatchAllHeader
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl :
Purpose :

SettingId : smtpFixAuthenticatedSenderHeaders
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpMaximumRecvThreads
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : threads
Purpose :

SettingId : smtpSMTPInboundMessageSize
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl : bytes
Purpose :

SettingId : smtpEnforceInboundMessageSize
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpInboundMessageRestriction
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : recipientsperhour
Purpose : Global limit for maximum number of SMTP recipients per hour.

SettingId : smtpSPFEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpSPFAction
SettingType : MailEnablePlatform
SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpSPFUseTrustedForwarders

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpSPFAllowBackupMX

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpSPFPassLocalIPs

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpSPFLocalPolicyStatus

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpSPFLocalPolicy

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl :

Purpose :

SettingId : smtpSPFBestGuessStatus

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpSPFBestGuessPolicy

SettingType : MailEnablePlatform
SettingDataType : string
SettingControl :
Purpose :

SettingId : smtpLocalSendersMustAuthenticate
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : smtpHideHeaderAddresses
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpScrambleWelcomeEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : smtpWelcomeMessage
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl :
Purpose :

SettingId : smtpResolveSenderDomain
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpSenderMustBeValid
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpAllowDomainLiterals
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpDisableCatchAlls
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpMaximumConversationErrors
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : dword
Purpose :

SettingId : smtpAutobanIPAddressesEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpRequirePTR
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : smtpEnforceInboundRecipientLimits
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : smtpMaximumInboundRecipients
SettingType : MailEnablePlatform
SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : smtpWhitelistOutboundIPAddresses

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpIPWhiteListingStatus

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpInboundRecipientLimitThresholdEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpInboundRecipientLimitThreshold

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : smtpOutboundFailedRecipientLimitThresholdEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : smtpOutboundFailedRecipientLimitThreshold

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : sysBadMailDirectory

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : path

Purpose :

SettingId : sysConfigurationDirectory

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : path

Purpose :

SettingId : sysSpamDirectory

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : path

Purpose :

SettingId : sysDataDirectory

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : path

Purpose :

SettingId : sysMailRoot

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : path

Purpose :

SettingId : sysCreateEmailsforAllDomains

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose : Publishes a mailbox address for each domain associated with the postoffice

SettingId : sysGeoIPEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : sysGeo-Login-Mode
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : sysGeo-Login-RestrictionType
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : sysGeo-Login-Restriction
SettingType : MailEnablePlatform
SettingDataType :
SettingControl : checklist
Purpose :

SettingId : sysIPv6Status
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose : Enables IPv6 options for this server

SettingId : sysProvisioningStatus
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose : Enables Provisioning - which allows additional actions to be performed when new organizations/domains/mailboxes are created

SettingId : sysDefaultTarpitPeriod
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : sysSkinCatalogueEnabled
SettingType : MailEnablePlatform

SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose : Determines whether the Management Console shows an online skin catalogue

SettingId : sysSpamStatsEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose : Determines whether Spam Stats are shown in the MailEnable Tray Utility

SettingId : sysSystemMessagesEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose : Determines whether the System Messages list is shown in the Management Console

SettingId : sysWebServices
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose : Determines whether the System Messages list is shown in the Management Console

SettingId : sysIOSAutoDetectEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose : Determines whether webmail detects IOS devices and presents advanced connectivity options

SettingId : sysIOSAutoConfigEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose : System will attempt to automatically detect domain/DNS settings for users connecting via iOS devices

SettingId : sysDefaultPostofficeEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose : If you enable the default postoffice, any username supplied without an @ symbol will be assumed to

belong to the default postoffice.

SettingId : sysDefaultPostoffice
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl : select
Purpose :

SettingId : sysSignUpStatus
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : sysAccountBindingMode
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : sysOutboundBindingMode
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : sysAuthLockoutMode
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : sysAuthLockoutValue
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : dword
Purpose :

SettingId : sysAuthPolicyStatus
SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : sysPasswordPolicyContainsLetter

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : sysPasswordPolicyContainsNumeric

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : sysPasswordPolicyContainsSymbol

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : sysPasswordPolicyMixedCase

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : sysMinimumPasswordLength

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : sysValidateCountry

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : retrievalDebugEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : retrievalDebugLogLevel
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : retrievalDebugLogFileDirectory
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl : path
Purpose :

SettingId : retrievalActivityLogEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : retrievalActivityLogDirectory
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl : path
Purpose :

SettingId : retrievalW3CLoggingEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : retrievalW3CLoggingRolloverFrequency
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select

Purpose :

SettingId : retrievalW3CLoggingDirectory

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : path

Purpose :

SettingId : retrievalPollInterval

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : seconds

Purpose :

SettingId : retrievalMaximumThreads

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : threads

Purpose :

SettingId : retrievalEmailHistoryRetention

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : days

Purpose :

SettingId : retrievalEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : retrievalIPv6Status

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : retrievalPostPickupDelay

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : milliseconds

Purpose :

SettingId : retrievalPostRetrieveMessageWait

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : milliseconds

Purpose :

SettingId : webmailPOPRetrieval

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webmailPreviewHTML

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webmailMailboxRedirection

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webmailAutoResponse

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webmailDisplayImagesInline

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webmailCanEditDisplayName
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webmailLoginDetails
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webmailAutoComplete
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webmailPasswordRecoveryEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webmailActivityViewEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webmailPublicFoldersEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webmailPollFrequency
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : milliseconds

Purpose :

SettingId : webmailShowUsage
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webmailDirectory
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webmailBrowserNotifications
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webmailSmallButtons
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : webmailShowLoginWallpaper
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webmailSMS
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webmailFiltering
SettingType : MailEnablePlatform

SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webmailFilterLimit

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : webmailHyperlinks

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webmailCalendaringEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webmailTasksEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webmailMaxDirectoryEntries

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : webmailMaxContacts

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : webmailFolderCaching
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webmailPersonalisationEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webmailMessageDeletionMode
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webmailMessagePreviewPane
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webmailMessagePopUpMenu
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webmailSpamFiltering
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webmailWhitelist
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webmailBlacklist

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webmailDownloadAll

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webmailMobileWebmailAssociationMode

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webmailSyncML

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webmailListHeaderCommandsEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webmailNotes

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webmailEmbedVideoLinks

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webmailMediaPlayerEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webmailAddNewRecipientsEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webmailIdentitiesEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webmailMailboxSearchEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webmailBannerStatus

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webmailFilterHTML

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webmailBlockRemoteImages
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webmailHideClientIP
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webmailPromptForMobile
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webmailServices
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webmailMultipleFileUpload
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webmailPublishAccessStatus
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webmailImportStatus
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled

Purpose : This enables users to configure the import of their mailbox from another server.

SettingId : webmailHelpStatus
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webmailHelpBase
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl : url
Purpose :

SettingId : webmailDefaultBase
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl : select
Purpose :

SettingId : webmailShares
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : webmailPublicFoldersModificationPermitted
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : webmailFileStoreEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : webmailSessionTimeOutStatus
SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : webmailCardDAVImportPermitted

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webmailCalDAVImportPermitted

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webmailIMAPImportPermitted

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webmailAutoSpellcheck

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : mobilewebmailAllowPersistentLogins

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webmailMessageReportAsSpam

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webmailMessageSpamAction
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : listAddListUnsubscribe
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : listBadMailBulkMessages
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : listDeniedPostingNotificationStatus
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : listDebugEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : listDebugLogLevel
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : listDebugLogFileDirectory
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl : path

Purpose :

SettingId : listActivityLogEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : listActivityLogDirectory

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : path

Purpose :

SettingId : sysChatStatus

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : sysChatBOSHStatus

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : sysChatXMPPStatus

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : sysProxyStatus

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : sysChatAdvertiseTLS

SettingType : MailEnablePlatform

SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : sysChatRequireTLS
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : sysHTTPUploadHost
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl :
Purpose :

SettingId : sysHTTPUploadPort
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : port
Purpose :

SettingId : sysChatGuestHost
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl :
Purpose :

SettingId : sysChatGuestPort
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : port
Purpose :

SettingId : sysChatGuestSSL
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : sysSOCKS5Host
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : dword
Purpose :

SettingId : sysSOCKS5HostPort
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : port
Purpose :

SettingId : sysChatMUCStatus
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : sysChatAllowGuests
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : sysChatAllowInvites
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : sysChatBOSHBinding
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl :
Purpose :

SettingId : sysChatHTTPUploadMaxFileSize
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : bytes

Purpose :

SettingId : sysChatSMTPHost

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl :

Purpose :

SettingId : sysChatSMTPPort

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : port

Purpose :

SettingId : sysChatCarbons

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : sysChatTime

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : sysChatStreamManagement

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : sysChatCSISStatus

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : sysChatMAMStatus

SettingType : MailEnablePlatform

SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : sysChatBlockingStatus
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : sysChatPubSubStatus
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : sysChatPEPStatus
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : sysChatPEPNotifyPresence
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : sysChatAdvertiseOMEMO
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : sysChatMaxRosterSize
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : dword
Purpose :

SettingId : poChatStatus
SettingType : MailEnablePostoffice
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : sysPasswordChangePolicy
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : poPasswordChangePolicy
SettingType : MailEnablePostoffice
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : mailboxPasswordChangePolicy
SettingType : MailEnableMailbox
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : sysDefaultCertificate
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl : select
Purpose :

SettingId : sysAbuseDetectionStatus
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : AuditingStatus
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : AuditingLevel
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : FooterPrecedence
SettingType : MailEnablePlatform
SettingDataType :
SettingControl : select
Purpose :

SettingId : FooterText
SettingType : MailEnablePlatform
SettingDataType :
SettingControl : textarea
Purpose :

SettingId : FooterHTML
SettingType : MailEnablePlatform
SettingDataType :
SettingControl : html
Purpose :

SettingId : sysLoginAuditing
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : sysMailboxAuditing
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : TwoFactorStatus
SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : TwoFactorAddressTypesConfigured

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : checklist

Purpose :

SettingId : sysFacebookStatus

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : select

Purpose :

SettingId : sysFacebookAppID

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl :

Purpose :

SettingId : sysFacebookAppSecret

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : password

Purpose :

SettingId : misInitialisationConcurrencyLimit

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl :

Purpose :

SettingId : misUpdateConcurrencyLimit

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl :

Purpose :

SettingId : popListenPort

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : popListenPortSSEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : popAlternatePortEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : popAlternatePort

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : popAlternatePortSSEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : popIPV6

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : popbinding

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : checklist

Purpose :

SettingId : popDebugEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : popDebugLogLevel
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : popDebugLogFileDirectory
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl : path
Purpose :

SettingId : popActivityLogEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : popActivityLogDirectory
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl : path
Purpose :

SettingId : popAPOPEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : popAlternateLoginChars
SettingType : MailEnablePlatform

SettingDataType : string

SettingControl :

Purpose :

SettingId : popClientTimeout

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : seconds

Purpose :

SettingId : popConcurrentAccessEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : popExtensions

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : checklist

Purpose :

SettingId : popInboundMaximumHeaderLength

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : popMaximumThreads

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : threads

Purpose :

SettingId : popScrambleWelcomeEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : popWelcomeMessage
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl :
Purpose :

SettingId : popAddReceivedHeader
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : popIPAccess
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : syncPublicFoldersEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : syncListenPort
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : dword
Purpose :

SettingId : syncCommandTimeOut
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : seconds
Purpose :

SettingId : syncIPv6Status
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : syncInboundServerBindings

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : checklist

Purpose :

SettingId : syncActivityLogEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : syncActivityLogDirectory

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : path

Purpose :

SettingId : syncDebugEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : syncDebugLogFileDirectory

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : path

Purpose :

SettingId : syncW3CLoggingEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : syncW3CLoggingDirectory

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : path

Purpose :

SettingId : syncW3CLoggingRolloverFrequency

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : syncDebugLoggingLevel

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : syncSyncMLStatus

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : syncIndexingEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : syncCardDAVStatus

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : syncFileRootEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : syncCalDAVStatus
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : syncAlternatePort
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : dword
Purpose :

SettingId : syncDAVDebug
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : syncDAVDebugPath
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl : path
Purpose :

SettingId : syncAlternatePortEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : syncListenPortSSEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : syncAlternatePortSSEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : syncStartupAndShutdownLoggingEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : syncAllowBasicAuthentication

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : syncAllowDigestAuthentication

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : syncCalDAVViaIIS

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : syncCardDAVViaIIS

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : syncSyncMLViaIIS

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : ldapAllowPersonalContacts

SettingType : MailEnablePlatform

SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : ldapSourceMode
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : easStatus
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : easDebug
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : easDebugPath
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl : path
Purpose :

SettingId : easDebugFilter
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl :
Purpose :

SettingId : easDebugFilterMode
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : easMaxWindowSize
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : changes
Purpose :

SettingId : syncAutodiscoverCustomisationEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : mtaDebugEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : mtaDebugLogLevel
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : mtaDebugLogFileDirectory
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl : path
Purpose :

SettingId : mtaActivityLogEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : mtaActivityLogDirectory
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl : path

Purpose :

SettingId : mtaInboundCommandMessageMaxDeliverTime

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : hours

Purpose :

SettingId : mtaMaximumTransferThreads

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : threads

Purpose :

SettingId : mtaPickupEventEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : mtaPickupEventTimeout

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : milliseconds

Purpose :

SettingId : mtaPickupEventCommand

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : commandpath

Purpose :

SettingId : sysQueueCampaigns

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : archiveStatus

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : archiveFolder

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl :

Purpose :

SettingId : archivePostoffice

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : select

Purpose :

SettingId : archiveMailbox

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : select

Purpose :

SettingId : pocDebugEnabled

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : pocDebugLogLevel

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : pocDebugLogFileDirectory

SettingType : MailEnablePlatform

SettingDataType : string

SettingControl : path

Purpose :

SettingId : pocActivityLogEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : pocActivityLogDirectory
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl : path
Purpose :

SettingId : pocEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : pocPollInterval
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : seconds
Purpose :

SettingId : pocPostPickupDelay
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : milliseconds
Purpose :

SettingId : pocAutoRespondersEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : pocAutoResponderReplyMode
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : select

Purpose :

SettingId : pocPostmasterReceivesMailWhenQuotaExceeded

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : pocQuotaEnumerationMode

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : pocSystemDefaultMailboxSizeLimit

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : pocMaximumPickupThreads

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : threads

Purpose :

SettingId : pocPostDeliveryThreadCreationDelay

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : milliseconds

Purpose :

SettingId : pocProcessMailboxEvents

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : pocMailboxDropEventCommandTimeOut

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : milliseconds

Purpose :

SettingId : pocProcessMailboxSpamFilters

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : pocProcessMailboxRules

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : pocNoNDRGeneration

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : pocForceRemailing

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : pocQuotaExceededNotificationMode

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : pocDeliveryEventAlways

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : webadminCampaignManagementEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webadminCampaignSubscriptionEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webadminDistributionsEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webadminDKIMManagementEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webadminMobileAssociationMode
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webadminSMSListEnabled
SettingType : MailEnablePlatform
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : webadminDefaultBase
SettingType : MailEnablePlatform
SettingDataType : string
SettingControl : select

Purpose :

SettingId : webadminSmallButtons

SettingType : MailEnablePlatform

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : poEnabled

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poWindowsAuthenticationEnabled

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poMappedDomainEnabled

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poMappedDomain

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : poUPNEnabled

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poWindowsAccountAutoCreation

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poForceValidWindowsCredentials

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poLocationReportingMode

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : select

Purpose : If enabled, configures whether we record details of mailbox access at a postoffice or mailbox level

SettingId : poRDNS

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poAntivirus

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poDelivery-DeliverToStatus

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poSMTP-GreyListing

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : poMailbox-JunkReport-Status
SettingType : MailEnablePostoffice
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : poWebMail-Shares
SettingType : MailEnablePostoffice
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : poWebMail-Public-Folders-Modification-Permitted
SettingType : MailEnablePostoffice
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : poWebMail-FileStoreEnabled
SettingType : MailEnablePostoffice
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : poWebMail-SessionTimeOutStatus
SettingType : MailEnablePostoffice
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : poWebMail-SmallButtons
SettingType : MailEnablePostoffice
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : poPublicFolders
SettingType : MailEnablePostoffice
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poRosterSource
SettingType : MailEnablePostoffice

SettingDataType : dword
SettingControl : select

Purpose :

SettingId : poWebMail-SpellcheckEmailsBeforeSending
SettingType : MailEnablePostoffice

SettingDataType : dword
SettingControl : select

Purpose :

SettingId : poWebMail-MessageSpamAction
SettingType : MailEnablePostoffice

SettingDataType : dword
SettingControl : select

Purpose :

SettingId : poPostoffice-PostofficeRulesStatus
SettingType : MailEnablePostoffice

SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poWebAdmin-CanEditMailboxes
SettingType : MailEnablePostoffice

SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poWebAdmin-CanEditLists
SettingType : MailEnablePostoffice

SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poWebAdmin-MaxLists
SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : poWebAdmin-MaxListMembers

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : poWebAdmin-CanEditDomains

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poWebAdmin-CanEditDirectoryEntries

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poWebAdmin-Branding

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poWebAdmin-MaxMailboxes

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : poWebAdmin-DefaultMailboxSize

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : unlimitedval

Purpose :

SettingId : poWebAdmin-CanEditMailboxSize
SettingType : MailEnablePostoffice
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : poWebAdmin-SmallButtons
SettingType : MailEnablePostoffice
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : poWebAdmin-Enabled
SettingType : MailEnablePostoffice
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : poSMTP
SettingType : MailEnablePostoffice
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : poPOP
SettingType : MailEnablePostoffice
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : poHTTPMail
SettingType : MailEnablePostoffice
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : poWebMail
SettingType : MailEnablePostoffice
SettingDataType : dword
SettingControl : select

Purpose :

SettingId : poIMAP

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : poMAPI

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : poActiveSync

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : poMailbox-Quota-Status

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poMailbox-Quota

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : poAgent-Purge-Postmaster-Inbox-Enabled

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poAgent-Purge-Postmaster-Inbox-Value

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : days

Purpose :

SettingId : poAgent-Purge-Postmaster-Inbox-DeleteUnread

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poSmarthostOutboundEnabled

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poSmarthostOutboundAuthenticationStatus

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poSmarthostOutboundHost

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : poSmarthostOutboundUsername

SettingType : MailEnablePostoffice

SettingDataType : string

SettingControl :

Purpose :

SettingId : poSmarthostOutboundPassword

SettingType : MailEnablePostoffice

SettingDataType : string

SettingControl : password

Purpose :

SettingId : poSmarthostRouteBiasMode
SettingType : MailEnablePostoffice
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : poFooterStatus
SettingType : MailEnablePlatform
SettingDataType :
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : poFooterText
SettingType : MailEnablePlatform
SettingDataType :
SettingControl : textarea
Purpose :

SettingId : poFooterHTML
SettingType : MailEnablePlatform
SettingDataType :
SettingControl : html
Purpose :

SettingId : poAgent-Purge-Inbox-Enabled
SettingType : MailEnablePostoffice
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : poAgent-Purge-Inbox-Value
SettingType : MailEnablePostoffice
SettingDataType : dword
SettingControl : days
Purpose :

SettingId : poAgent-Purge-Inbox-DeleteUnread
SettingType : MailEnablePostoffice
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poAgent-Purge-Deleted-Enabled

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poAgent-Purge-Deleted-Value

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : days

Purpose :

SettingId : poAgent-Purge-Deleted-DeleteUnread

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poAgent-Purge-Sent-Enabled

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poAgent-Purge-Sent-Value

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : days

Purpose :

SettingId : poAgent-Purge-Sent-DeleteUnread

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poAgent-Purge-Junk-Enabled

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poAgent-Purge-Junk-Value

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : days

Purpose :

SettingId : poAgent-Purge-Junk-DeleteUnread

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poSMTP-Inbound-Message-UsageRestrictionEnabled

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poSMTP-Inbound-Message-UsageRestriction

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : recipientsperhour

Purpose :

SettingId : poLocalDeliveryRequiresAuthentication

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poPostoffice-Quota-Limit-Enabled

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poPostoffice-Quota-LimitMB
SettingType : MailEnablePostoffice
SettingDataType : dword
SettingControl : megabytes
Purpose :

SettingId : poPostoffice-Quota-Notification-Threshold
SettingType : MailEnablePostoffice
SettingDataType : dword
SettingControl : percent
Purpose :

SettingId : poPostoffice-Quota-Notification-Mailbox
SettingType : MailEnablePostoffice
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : poGeo-Login-RestrictionType
SettingType : MailEnablePostoffice
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : poGeo-Login-Restriction
SettingType : MailEnablePostoffice
SettingDataType :
SettingControl : checklist
Purpose :

SettingId : poTwoFactorStatus
SettingType : MailEnablePostoffice
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : poMigrationCalDAVURL
SettingType : MailEnablePostoffice
SettingDataType : string
SettingControl :

Purpose :

SettingId : poMigrationCardDAVURL

SettingType : MailEnablePostoffice

SettingDataType : string

SettingControl :

Purpose :

SettingId : poMigrationIMAPServer

SettingType : MailEnablePostoffice

SettingDataType : string

SettingControl :

Purpose :

SettingId : poMigrationIMAPPort

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : poMigrationIMAPSSL

SettingType : MailEnablePostoffice

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poFacebookStatus

SettingType : MailEnablePostoffice

SettingDataType : string

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : poFacebookAppID

SettingType : MailEnablePostoffice

SettingDataType : string

SettingControl :

Purpose :

SettingId : poFacebookAppSecret

SettingType : MailEnablePostoffice

SettingDataType : string

SettingControl : password

Purpose :

SettingId : mailboxRedirectionStatus

SettingType : MailEnableMailbox

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose : Enables or disables mailbox redirection.

SettingId : mailboxRedirectionAddress

SettingType : MailEnableMailbox

SettingDataType : string

SettingControl : Semi-colon delimited list of e-mail addresses

Purpose : Provides a list of e-mail addresses that a mailbox is redirecting to.

SettingId : mailboxLimit

SettingType : MailEnableMailbox

SettingDataType : dword

SettingControl : kilobytes (-1 for unlimited where applicable)

Purpose : Specifies the quota for the mailbox in kilobytes (or -1 is unlimited).

SettingId : mailboxSizeUsage

SettingType : MailEnableMailbox

SettingDataType : dword

SettingControl : kilobytes (-1 for unlimited where applicable)

Purpose :

SettingId : mailboxStatus

SettingType : MailEnableMailbox

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose : Determines whether a mailbox can receive e-mail (and can be accessed).

SettingId : mailboxPublish

SettingType : MailEnableMailbox

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose : Determines whether a mailbox is advertised in the directory.

SettingId : mailboxPassword
SettingType : MailEnableMailbox
SettingDataType : string
SettingControl : password
Purpose :

SettingId : mailboxRights
SettingType : MailEnableMailbox
SettingDataType : string
SettingControl :
Purpose :

SettingId : mailboxLoginStatus
SettingType : MailEnableMailbox
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose : Determines whether a mailbox can be accessed via login.

SettingId : mailboxPriority
SettingType : MailEnableMailbox
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose : Determines whether a mailbox receives message delivery priority over other mailboxes.

SettingId : mailboxDisplayName
SettingType : MailEnableMailbox
SettingDataType : string
SettingControl :
Purpose :

SettingId : mailboxTimeZone
SettingType : MailEnableMailbox
SettingDataType : string
SettingControl :
Purpose : Provides a string representing the mailbox time zone. Example: Mountain Standard Time

SettingId : mailboxWebMailStartupPage
SettingType : MailEnableMailbox
SettingDataType : string

SettingControl :

Purpose :

SettingId : mailboxGroups

SettingType : MailEnableMailbox

SettingDataType : string

SettingControl :

Purpose :

SettingId : mailboxWebMailWatermarkURL

SettingType : MailEnableMailbox

SettingDataType : string

SettingControl :

Purpose : Provides a relative path to background skins for webmail. example:
Watermarks/Sky.jpg.

SettingId : mailboxWebMailInterfaceOpacity

SettingType : MailEnableMailbox

SettingDataType : string

SettingControl :

Purpose :

SettingId : mailboxTimeZone

SettingType : MailEnableMailbox

SettingDataType : string

SettingControl :

Purpose : Provides a string representing the mailbox time zone. Example: Mountain
Standard Time

SettingId : mailboxTwoFactorModel

SettingType : MailEnableMailbox

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : mailboxTwoFactorAddress

SettingType : MailEnableMailbox

SettingDataType : string

SettingControl :

Purpose :

SettingId : mailboxTwoFactorAddressType
SettingType : MailEnableMailbox
SettingDataType : string
SettingControl : select
Purpose :

SettingId : mailboxTwoFactorQRCode
SettingType : MailEnableMailbox
SettingDataType : string
SettingControl : QRCode
Purpose :

SettingId : mailboxStartWorkDay
SettingType : MailEnableMailbox
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : mailboxEndWorkDay
SettingType : MailEnableMailbox
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : mailboxWorkDaysOnly
SettingType : MailEnableMailbox
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : mailboxStartDayHour
SettingType : MailEnableMailbox
SettingDataType : dword
SettingControl : dword
Purpose :

SettingId : mailboxEndDayHour
SettingType : MailEnableMailbox
SettingDataType : dword
SettingControl : dword

Purpose :

SettingId : mailboxStartWorkTime
SettingType : MailEnableMailbox
SettingDataType : dword
SettingControl : dword
Purpose :

SettingId : mailboxEndWorkTime
SettingType : MailEnableMailbox
SettingDataType : dword
SettingControl : dword
Purpose :

SettingId : mailboxSMTP
SettingType : MailEnableMailbox
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : mailboxPOP
SettingType : MailEnableMailbox
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : mailboxHTTPMail
SettingType : MailEnableMailbox
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : mailboxWebMail
SettingType : MailEnableMailbox
SettingDataType : dword
SettingControl : select
Purpose :

SettingId : mailboxIMAP
SettingType : MailEnableMailbox

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : mailboxMAPI

SettingType : MailEnableMailbox

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : mailboxActiveSync

SettingType : MailEnableMailbox

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : mailboxChatStatus

SettingType : MailEnableMailbox

SettingDataType : dword

SettingControl : select

Purpose :

SettingId : mailboxMustChangePassword

SettingType : MailEnableMailbox

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : listListType

SettingType : MailEnableList

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : listListStatus

SettingType : MailEnableList

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : listDescription
SettingType : MailEnableList
SettingDataType : string
SettingControl :
Purpose :

SettingId : listHeaderAnnotationStatus
SettingType : MailEnableList
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : listHeaderAnnotation
SettingType : MailEnableList
SettingDataType : string
SettingControl :
Purpose :

SettingId : listFooterAnnotationStatus
SettingType : MailEnableList
SettingDataType : dword
SettingControl : 0=Disabled, 1=Enabled
Purpose :

SettingId : listFooterAnnotation
SettingType : MailEnableList
SettingDataType : string
SettingControl :
Purpose :

SettingId : listModeratorAddress
SettingType : MailEnableList
SettingDataType : string
SettingControl : sysaddress
Purpose :

SettingId : listListAddress
SettingType : MailEnableList
SettingDataType : string
SettingControl : sysaddress

Purpose :

SettingId : listSubscribeMessageFileStatus

SettingType : MailEnableList

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : listSubscribeMessageFile

SettingType : MailEnableList

SettingDataType : string

SettingControl :

Purpose :

SettingId : listUnsubscribeMessageFileStatus

SettingType : MailEnableList

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : listUnsubscribeMessageFile

SettingType : MailEnableList

SettingDataType : string

SettingControl :

Purpose :

SettingId : listSubjectSuffixStatus

SettingType : MailEnableList

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : listSubjectSuffix

SettingType : MailEnableList

SettingDataType : string

SettingControl :

Purpose :

SettingId : listSubjectPrefix

SettingType : MailEnableList

SettingDataType : string

SettingControl :

Purpose :

SettingId : listSubjectPrefixStatus

SettingType : MailEnableList

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : listOwner

SettingType : MailEnableList

SettingDataType : string

SettingControl : sysaddress

Purpose :

SettingId : listHelpFileStatus

SettingType : MailEnableList

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : listHelpMessageFile

SettingType : MailEnableList

SettingDataType : string

SettingControl :

Purpose :

SettingId : listRemovalMessageFile

SettingType : MailEnableList

SettingDataType : string

SettingControl :

Purpose :

SettingId : listRemovalMessageFileStatus

SettingType : MailEnableList

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : listPostingMode
SettingType : MailEnableList
SettingDataType : dword
SettingControl : dword
Purpose :

SettingId : listMaxMessageSize
SettingType : MailEnableList
SettingDataType : dword
SettingControl : dword
Purpose :

SettingId : listReplyToMode
SettingType : MailEnableList
SettingDataType : dword
SettingControl : dword
Purpose :

SettingId : listDigestMailbox
SettingType : MailEnableList
SettingDataType : string
SettingControl :
Purpose :

SettingId : listDigestMode
SettingType : MailEnableList
SettingDataType : dword
SettingControl : dword
Purpose :

SettingId : listPassword
SettingType : MailEnableList
SettingDataType : string
SettingControl :
Purpose :

SettingId : listAuthenticationMode
SettingType : MailEnableList
SettingDataType : dword
SettingControl : dword

Purpose :

SettingId : listSubSubscriptionMode

SettingType : MailEnableList

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : listFromAddressMode

SettingType : MailEnableList

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : listDigestSchedulingInterval

SettingType : MailEnableList

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : listDigestSchedulingMode

SettingType : MailEnableList

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : listDigestSchedulingStatus

SettingType : MailEnableList

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : listDigestMessageSeparationMode

SettingType : MailEnableList

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : listDigestAttachmentMode

SettingType : MailEnableList

SettingDataType : dword

SettingControl : dword

Purpose :

SettingId : domainStatus

SettingType : MailEnableDomain

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : domainRedirectionStatus

SettingType : MailEnableDomain

SettingDataType : dword

SettingControl : 0=Disabled, 1=Enabled

Purpose :

SettingId : domainRedirectionHosts

SettingType : MailEnableDomain

SettingDataType : string

SettingControl : hostlist

Purpose :